

SPECIFICATIONS

INPUT CONNECTORS one pair Balanced, one pair single-ended

SPEAKER CONNECTORS four pairs of Hurricane loudspeaker outputs banana-plug sockets per channel, except on 230 VAC version

CONTROL I/O Ethernet, RS-232, Trigger In and Out, USB-A, Mini USB

RATED OUTPUT POWER 250 wpc RMS @ 8 Ω , 20Hz to 20kHz @ <0.3% THD, full output from 2.83VRMS

FREQUENCY RESPONSE 10Hz to 20kHz \pm 0.2dB

SIGNAL-TO-NOISE RATIO >85dB, reference level: 2.83 VRMS

INPUT IMPEDANCE 60 k Ω balanced; 30 k Ω unbalanced

VOLTAGE GAIN 26dB

INPUT SENSITIVITY 2.83VRMS output at 142mVRMS input

POWER REQUIREMENTS 100V~, 120V~, 230V~, factory set for destination country, 1500W

DIMENSIONS

Height (with feet): 7.75" (19.7cm)

Height (without feet): 7" (17.8cm)

Width: 17.75" (45.1cm)

Depth: 20" (50.8cm)

WEIGHT Net weight: 107 lbs (48.5kg) Shipping weight: 124 lbs (56.3kg)