

| | |
|---|------------------------------|
| Minimum RMS Output Power (8 ohms, 20 Hz-20 kHz) | 100 W + 100 W (0.019% THD) |
| Potenza d'uscita massima (4 ohms, 1kHz, 0.7% THD, for Europe) | 160 W + 160 W |
| Potenza dinamica elevata/canale (8/6/4/2 ohms) | 140/170/220/290 W |
| Fattore di smorzamento | 240 |
| Risposta in frequenza | 10 Hz-100 kHz +/-1.0 dB |
| Distorsione armonica totale(CD to Sp Out, 20 Hz-20 kHz) | 0.019% (50 W/8 ohms) |
| Rapporto segnale/rumore (CD) | 99dB (input shorted, 200 mV) |
| Audio In / Out | 8 / 2 |
| Digital Input | Si (optical / coaxial) |
| Subwoofer Out | Si |
| DC out | Si |
| Pure Direct | Si |
| ToP-ART (Total Purity Audio Reproduction Technology) | Si |
| Amplificazione diretta CD commutabile | Si |
| Standby Power Consumption | 0.5W |
| Power Management (Auto Power Standby) | Si |
| Dimensioni (L x A x P mm) | 435 x 151 x 387 mm; |
| Peso | 11.2 kg |