

## **ELECTRONIC SPECIFICATIONS**

### **POWER OUTPUT PER CHANNEL**

200W @ 4 or 8 Ohms

### **NUMBER OF CHANNELS**

5 (can also be used as a 2-zone amplifier with 3 channels in zone A and 2 channels in zone B)

### **TOTAL HARMONIC DISTORTION**

0.005%

### **S/N BELOW RATED OUTPUT**

112dB

### **DYNAMIC HEADROOM**

1.7dB

### **DAMPING FACTOR**

>140

### **RATED POWER BAND**

20Hz to 20kHz

### **FREQUENCY RESPONSE**

+0, -0.25dB from 20Hz to 20,000Hz

+0, -3dB from 10Hz to 100,000Hz

## **CONTROL**

### **REMOTE POWER CONTROL**

Yes, 5 or 3 + 2 Channel

### **MULTI-CHANNEL DB25 CABLE**

Yes

## **GENERAL SPECIFICATIONS**

### **CIRCUIT CONFIGURATION**

Push-Pull Complementary

### **CIRCUIT DESIGN**

Transistor

### **MONO BRIDGE**

No

### **MONO PARALLEL**

No

### **AUTOFORMER**

No

### **METERS**

Yes

### **METER LIGHT SWITCH**

Yes

### **BALANCED INPUT**

Yes

### **FRONT PANEL**

Glass

### **ILLUMINATION**

LED Fiber Optic

### **CHASSIS STYLE**

Inverted

**GOLD PLATED BINDING POSTS**

Yes

**WEIGHTS & DIMENSIONS**

**DIMENSIONS (W X H X D)**

17-1/2" (44.45cm) x 9-7/16" (23.97cm) (including feet) x 21" (53.3cm) (including front panel and cables)

**WEIGHT**

81 lbs (44.2 kg)

**SHIPPING WEIGHT**

114 lbs (51.8 kg)