

ELECTRONIC SPECIFICATIONS

POWER OUTPUT PER CHANNEL

200W @ 4 or 8 Ohms

NUMBER OF CHANNELS

7 (can also be used as a 2-zone amplifier with 5 channels in zone A and 2 channels in zone B)

TOTAL HARMONIC DISTORTION

0.005%

S/N BELOW RATED OUTPUT

112dB

DYNAMIC HEADROOM

1.7dB

DAMPING FACTOR

>140

RATED POWER BAND

20Hz to 20kHz

FREQUENCY RESPONSE

+0, -0.25dB from 20Hz to 20,000Hz

+0, -3dB from 10Hz to 100,000Hz

CONTROL

REMOTE POWER CONTROL

Yes, 7 or 5 + 2 Channel

MULTI-CHANNEL DB25 CABLE

Yes

GENERAL SPECIFICATIONS

CIRCUIT CONFIGURATION

Push-Pull Complementary

CIRCUIT DESIGN

Transistor

MONO BRIDGE

No

MONO PARALLEL

No

AUTOFORMER

No

METERS

Yes

METER LIGHT SWITCH

Yes

BALANCED INPUT

Yes

FRONT PANEL

Glass

ILLUMINATION

LED Fiber Optic

CHASSIS STYLE

Inverted

GOLD PLATED BINDING POSTS

Yes

WEIGHTS & DIMENSIONS

DIMENSIONS (W X H X D)

17-1/2" (44.5cm) x 9-7/16" (23.9cm) (including feet) x 21" (53.3cm) (including front panel and cables)

WEIGHT

83 lbs (37.6 kg)

SHIPPING WEIGHT

116 lbs (52.6 kg)