

- Qty Included Pair
- Orientation Vertical
- Height 11.71" (29.74 cm)
- Width 6.5" (16.51 cm)
- Depth 11.97" (30.4 cm)
- Driver Enclosure Type MDF cabinet with extruded natural bead-blasted aluminium front baffle
- Driver Complement
 - (1) 5.25" (13.34 cm) d (Round) Polypropylene BDSS Bass - Mid/Woofer
 - (1) 1" (2.54 cm) d (Round) Annealed Aluminium Dome and Laterally Offset - Tweeter
 - (1) 5" (12.7 cm) h x 9" (22.86 cm) w (Oval) Passive - Bass Radiator

Audio Quality

- Total Frequency Response 44 Hz → 24,000 Hz
- Nominal Impedance 8 ohms
- Sensitivity (1 watt @ 1 metre) 88 dB
- Lower and Upper -3dB Limits 64 Hz → 22,000 Hz

Inputs

- Audio Inputs
- Speaker Inputs (1) (Set) 5-Way Binding Posts - Gold Plated

On-Stand Mount

- Mounting Type 1/4 in - 20 Threaded Insert
- Available Orientations Vertical
- Mounting Location Bottom of Speakers

On-Shelf Mount

- Mounting Type
- Available Orientations Vertical

External Amplifier

- Recommended Amplifier Power Per Channel 20 watts → 150 watts

Crossover

- A/V Receiver Crossover Settings Small (80 Hz)