

## Electronic Specifications

- Power Output per Channel  
1200 Watts @ 2, 4 or 8 Ohms
- Number of Channels  
1
- Total Harmonic Distortion  
0.005%
- S/N below rated output  
Balanced: 124dB  
Unbalanced: 120dB
- Dynamic Headroom  
2.2dB
- Damping Factor  
>40 Wideband
- Rated Power Band  
20Hz to 20kHz
- Frequency Response  
+0, -0.25dB from 20Hz to 20,000Hz  
+0, -3dB from 10Hz to 100,000Hz

## Control

- Remote Power Control  
Yes
- Multi-Channel DB25 Cable  
N/A

## General Specifications

- Circuit Configuration  
Quad Balanced
- Circuit Design  
Solid State
- Mono Bridge  
N/A
- Mono Parallel  
N/A
- Output Type  
Autoformer™
- Meters  
Yes
- Meter Light Switch  
Yes
- Balanced Input  
1
- Front Panel  
1/2" Glass with handles
- Illumination  
Direct LED
- Chassis Style

Polished stainless steel & black painted steel

### **Connectivity**

- Speaker Binding Post Type  
Patented Solid Cinch™ Speaker Binding Posts

### **Weights & Dimensions**

- Dimensions (W x H x D)  
17-3/4" (45.09cm) x 12-5/16" (31.27cm) (including feet) x 22" (55.88cm) (including the front panel and cables)
- Weight  
158 lbs (71.7 kg)
- Shipping Weight  
184 lbs (83.4 kg)