

• **Electronic Specifications**

- Power Output per Channel
300 Watts @ 2, 4 or 8 Ohms
- Number of Channels
2
- Total Harmonic Distortion
0.005%
- S/N below rated output
120dB
- Dynamic Headroom
2.3dB
- Damping Factor
>40 Wideband
- Rated Power Band
20Hz to 20kHz
- Frequency Response
+0, -0.25dB from 20Hz to 20,000Hz
+0, -3.0dB from 10Hz to 100,000Hz

Control

- Remote Power Control
Yes
- Multi-Channel DB25 Cable
N/A

Connectivity

- Speaker Binding Post Type
Patented Solid Cinch™ Speaker Binding Posts

General Specifications

- Circuit Configuration
Push-Pull Complementary
- Circuit Design
Solid State
- Mono Bridge
No
- Mono Parallel
No
- Output Type
Autoformer™
- Meters
Yes
- Meter Light Switch
Yes
- Balanced Input
2
- Front Panel

- Glass
- Illumination
Direct LED
- Chassis Style
Polished stainless steel & black painted steel

Weights & Dimensions

- Dimensions (W x H x D)
17-1/2" (44.45cm) x 9-7/16" (23.97cm) (including feet) x 22" (55.88cm) (including front panel, handles and cables)
- Weight
105 lbs (47.63 kg)
- Shipping Weight
138 lbs (62.59 kg)

-