

• **Electronic Specifications**

- Power Output per Channel
250 Watts into 8 Ohms
300 Watts into 4 Ohms
- Number of Channels
4
- Total Harmonic Distortion
0.025%
- S/N below rated output
100dB
- Dynamic Headroom
8 Ohms: 2.5dB
4 Ohms: 3.5dB
- Damping Factor
8 Ohms: >85
4 Ohms: >45
- Rated Power Band
20Hz to 20kHz
- Frequency Response
+0, -0.9dB from 20Hz to 20,000Hz

Control

- Remote Power Control
Yes
- Multi-Channel DB25 Cable
N/A

Connectivity

- Speaker Binding Post Type
Standard

General Specifications

- Circuit Configuration
Closed loop digital switching
- Circuit Design
Digital
- Mono Bridge
N/A
- Mono Parallel
N/A
- Output Type
Direct Coupled
- Meters
Yes
- Meter Light Switch
No
- Balanced Input

- 4
- Front Panel
Glass with removable rack mounting ears
- Illumination
Direct LED
- Chassis Style
Black painted steel

Weights & Dimensions

- Dimensions (W x H x D)
17-1/2" (44.45cm) (19" (48.3cm with mounting ears)) x 4-5/16" (11cm) (including feet) x 21" (53.3cm) (including front panel and cables)
- Weight
23.5 lbs (10.7 kg)
- Shipping Weight
40 lbs (18.1 kg)

-