

Stellar Phono

Unit Weight	21.6lbs. (9.8 kg)
Unit Dimensions	17"W x 13"D x 3.25"H (43cm x 33.02cm x 8.255cm)
Shipping Weight	25.1lbs (11.4 kg)
Shipping Dimensions	22"W x 8"H x 17"D (55.88cm x 43.18cm x 20.32cm)
Color Options	Black Silver
Voltage Options (Factory set only)	Japan 100V North America 120V Europe/Asia/Australia/New Zealand 230V
Mains Power Input	IEC C14
Idle Power Consumption	26W
Fuses	100V: T250V-2.0AH (2A Slow Blow) 120V: T250V-1.6AH (1.6A Slow Blow) 230V: T250V-1AH (1A Slow Blow)
Accessories Included	US (NEMA 5-15P) (100V/120V versions) Schuko (CEE7/7) (230V version) UK (BS1363) (230V version) Remote Control
Audio Inputs	RCA (Unbalanced) MM,MC
Audio Outputs	RCA (Unbalanced) 1 Stereo Pair XLR (Balanced) 1 Stereo Pair
DC Trigger	3.5mm 12VDC (2)
Performance	All measurements are with both channels operating, gain set to low, and balanced outputs. Input frequency is 1kHz.
Gain	MM: 44dB, 50dB, 56dB MC: 60dB, 66dB, 72dB
Input Loading	MM: 47K Ω (100pF) MC: 60 Ω , 100 Ω , 200 Ω , 47K Ω , Custom 1-1K Ω
Output Impedance	Unbalanced <200 Ω Balanced <200 Ω per leg
Frequency Response	20Hz - 20KHz +/- 0.25dB
THD	0.5V out @ 1kHz: <0.01%
Maximum Output	@ 1% THD: 24VRMS
Overload Margin	@ 1kHz: >22dB
S/N Ratio	MM: >82dB A-Weighted MC: >74dB A-Weighted
Interchannel Crosstalk	>74dB
Power Consumption	26W