

Playable disc types	Super Audio CD, CD (including CD-R and CD
Analog audio outputs	
XLR/ESL-A	1 pair (L/R)
Output impedance	114Ω
Maximum output level	5.0Vrms (1kHz, 10kΩ loaded)
RCA	1 pair (L/R)
Output impedance	34Ω
Maximum output level	2.5Vrms (1kHz, 10kΩ loaded)
Digital audio outputs	
XLR	1
Output impedance	3Vp-p (110Ω loaded)
Output signal formats	Linear PCM (AES/EBU) 44.1kHz, 16-bit (CD)
RCA	1
Output impedance	0.5Vp-p (75Ω loaded)
Output signal formats	Linear PCM (IEC60958) 44.1kHz, 16-bit (CD)
Digital audio inputs	
RCA	1
Input signal formats	
Linear PCM	32k to 192kHz, 16/24-bit (IEC60958)
DSD	2.8MHz (DoP)
OPTICAL	1
Input signal formats	
Linear PCM	32k to 192kHz, 16/24-bit (IEC60958)
DSD	2.8MHz (DoP)
USB B	1 (USB2.0 supported)
Input signal formats	
Linear PCM	44.1k to 384kHz, 16/24/32-bit (IEC60958)
DSD	2.8MHz, 5.6MHz, 11.2MHz, 22.5MHz
Clock input	
BNC	1
Input impedance	50Ω
Frequencies that can be input (±10ppm)	10MHz
Input level	0.5 to 1.0Vrms (Sine wave)
External control interface	
RS-232C	1 (Please see here for command table)
Trigger	1 (3.5mm Monaural mini jack)
General	
Power supply	
Model for Europe	AC 220 to 240V, 50/60Hz
Model for US/Canada	AC 120V, 60Hz
Model for Korea	AC 220V, 60Hz
Model for Hong Kong	AC 230V, 50Hz
Power consumption	25W
External dimensions (W×H×D)	445 × 162 × 438mm

Weight

Included accessories

17- $\frac{5}{8}$ " \times 6- $\frac{1}{2}$ " \times 17- $\frac{1}{4}$ " (including protrusions)

28kg / 61- $\frac{3}{4}$ lb

Power cord set \times 1

Remote control (RC-1333) \times 1

AAA batteries \times 2

Felt pads \times 3

Owner's manual \times 1

Warranty card \times 1