

|                                     |   |
|-------------------------------------|---|
| <b>Type</b>                         | 3-speed, fully manual operation   |
| <b>Motor</b>                        | DC servo motor  |
| <b>Drive Method</b>                 | Direct drive  |
| <b>Speeds</b>                       | 33-1/3 RPM, 45 RPM, 78 RPM  |
| <b>Turntable Platter</b>            | Die-cast aluminum   |
| <b>Starting Torque</b>              | >1.0 kgf.cm   |
| <b>Braking System</b>               | Electronic brake  |
| <b>Wow and Flutter</b>              | <0.2% (WTD) @ 3 kHz (JIS)   |
| <b>Signal-to-Noise Ratio</b>        | >50 dB  |
| <b>Output Level</b>                 | Pre-amp "PHONO": 4 mV nominal at 1 kHz, 5 cm/sec<br>Pre-amp "LINE": 240 mV nominal at 1 kHz, 5 cm/sec   |
| <b>Phono Pre-Amp Gain</b>           | 36 dB nominal, RIAA equalized   |
| <b>USB Function</b>                 | A/D, D/A – 16-bit/44.1 kHz or 48 kHz USB selectable; Computer interface – USB 2.0 C or above  |
| <b>Power Supply Requirements</b>    | 100 to 240 V, 50/60 Hz, 1.5A Max  |
| <b>Power Consumption</b>            | 2.75 W  |
| <b>Dimensions</b>                   | 452.0 mm (17.80") W x 352.0 mm (13.86") D x 141.6 mm (5.57") H  |
| <b>Weight</b>                       | 8 kg (17.6 lbs.), without dust cover  |
| <b>Accessories Included</b>         | AT-VM95E phono cartridge; AT-HS6 headshell; 1.9 m (6.2') USB cable; dual RCA (ma counterweight; felt mat; dust cover; 45 RPM adapter; plug-type stylus target light |
| <b>Tonearm Type</b>                 | Balanced S-shaped tonearm with detachable headshell   |
| <b>Effective Arm Length</b>         | 230.5 mm  |
| <b>Overhang</b>                     | 16 mm   |
| <b>Tracking Error Angle</b>         | Less than 3 degrees   |
| <b>Applicable Cartridge Weight</b>  | 3.5-8.5 g   |
| <b>Anti-skating Range</b>           | 0-4 g   |
| <b>Replacement Stylus</b>           | AT-VMN95E   |
| <b>Communication System</b>         | Bluetooth Version 5.0   |
| <b>Maximum Communication Range</b>  | Line of sight - approx. 10 m (33')  |
| <b>Compatible Bluetooth Profile</b> | A2DP  |
| <b>Support Codec</b>                | SBC, Qualcomm® aptX™ audio  |