

Electronic Specifications

- Power Output per Channel
150W @ 2, 4 or 8 Ohms
- Number of Channels
2
- Total Harmonic Distortion
0.5% maximum harmonic distortion at any power level from 250 milliwatts to rated power,
20Hz to 20,000Hz
<0.20% at 1W, 20Hz to 20,000Hz
- S/N below rated output
112dB
- Dynamic Headroom
1.2dB
- Damping Factor
>18
- Rated Power Band
20Hz to 20kHz
- Frequency Response
+0, -0.25dB from 20Hz to 20,000Hz
+0, -3dB from 10Hz to 70,000Hz

Control

- Remote Power Control
Yes
- Multi-Channel DB25 Cable
N/A

Connectivity

- Speaker Binding Post Type
Patented Solid Cinch™ Speaker Binding Posts

General Specifications

- Circuit Configuration
Unity Coupled
- Circuit Design
Vacuum Tube
- Mono Bridge
No
- Mono Parallel
No
- Output Type
Unity Coupled Output Transformer
- Meters
No
- Meter Light Switch
N/A
- Balanced Input

- 2
- Front Panel
N/A
- Illumination
Small Signal Tubes: Green, Natural
- Chassis Style
Polished Stainless Steel

Weights & Dimensions

- Dimensions (W x H x D)
18-1/4" (46.4cm) x 10-1/4" (26cm) (including feet) x 21" (53.3cm)
- Weight
118 lbs (53.5 kg)
- Shipping Weight
135 lbs (61.2 kg)