

- Detachable Grilles Yes
- System Components 2 speakers
- Amplification Type passive, active bass driver
- Crossover Channel Qty 3-way
- Frequency Response 25 - 26000 Hz
- -3dB Frequency Response 36 Hz
- Nominal Impedance 8 Ohm
- Recommended Amplifier Power 30 Watt
- Sensitivity 90 dB
- Output Features Power Port
- Audio Amplifier integrated
- Active Bass Driver Amplifier Power 160 Watt
- Magnetic Shield Yes
- Connectivity Technology wired
- Recommended Placing floor-standing
- Controls subwoofer cut frequency, subwoofer volume control

Compatibility | Accessories

- Type none

Speaker System Details

- Speaker Qty 2
- Frequency Response 25 Hz
- Input Impedance 8 Ohm
- Recommended Placing floor-standing
- Connectivity Technology wired
- Crossover Channel Qty 3-way

Driver Details (1st speaker)

- Speaker Type speaker
- Driver Type mid/woofer driver, subwoofer driver, tweeter driver
- Driver Qty 1
- Driver Diameter 1 m, 6.5 m
- Driver Diameter (metric) 165 mm, 25 mm
- Driver Technology / Design Dynamic Balance

Dimensions & Weight

- Width 8 in
- Depth 13 in
- Height 42.3 in

Dimensions & Weight Details

- Width 8 in
- Depth 13 in
- Height 42.3 in