

## • **Electronic Specifications**

- Power Output per Channel  
350W @ 2, 4 or 8 Ohms
- Number of Channels  
1
- Total Harmonic Distortion  
0.3% maximum harmonic distortion at any power level from 250 milliwatts to rated power,  
20Hz to 20,000Hz  
<0.20% at 1W, 20Hz to 20,000Hz
- S/N below rated output  
120dB
- Dynamic Headroom  
2.4dB
- Damping Factor  
>25 Wideband
- Rated Power Band  
20Hz to 20kHz
- Frequency Response  
+0, -0.5dB from 20Hz to 20,000Hz  
+0, -3.0dB from 10Hz to 70,000Hz

## **Control**

- Remote Power Control  
Yes
- Multi-Channel DB25 Cable  
N/A

## **General Specifications**

- Circuit Configuration  
Unity Coupled
- Circuit Design  
Vacuum Tube
- Mono Bridge  
No
- Mono Parallel  
No
- Output Type  
Unity Coupled Output Transformer
- Meters  
Yes
- Meter Light Switch  
Yes
- Balanced Input  
Yes
- Front Panel  
Machined aluminum with handles
- Illumination  
Direct LED

- Chassis Style  
Polished stainless steel

### **Connectivity**

- Speaker Binding Post Type  
Patented Solid Cinch™ Speaker Binding Posts

### **Weights & Dimensions**

- Unit Dimensions (W x H x D)  
18" (45.7cm) x 11-13/16" (30cm) x 21-5/8" (54.9cm)
- Unit Weight  
121 lbs (54.9 kg)
- Shipping Weight  
147 lbs (66.7 kg)