

Spec description

Amplifier section

Practical maximum output 260W + 260W (4Ω, 1kHz, JEITA)

170W + 170W (8Ω, 1kHz, JEITA)

Rated output 230W + 230W (4Ω, 1kHz, THD 1%)

125W + 125W (8Ω, 1kHz, THD 1%)

Total harmonic distortion 0.003% (8Ω, 1kHz, 55W, JEITA)

S/N ratio 110dB (8Ω, 1kHz, IHF-A)

Frequency response 10Hz to 50,000Hz (+0dB, -6dB, 8Ω, JEITA)

Analog audio inputs

Balanced

Connectors XLR (HOT: 2) × 1 pair

Input sensitivity 1.6V

Input impedance 64kΩ (in STEREO mode), 32kΩ (in BI-AMP mode)

Unbalanced

Connectors RCA (gold-plated) × 1 pair

Input sensitivity 1.6V

Input impedance 32kΩ (in STEREO mode), 16kΩ (in BI-AMP mode)

Speaker output

Connectors Screw type × 1 pair (gold-plate, compatible with Banana plug)

Compatible speaker impedance 4Ω to 8Ω

External control

Trigger input (12V TRIGGER IN)

Connector 3.5mm Mono mini jack × 1

Input level 12V, 1mA

Trigger output (12V TRIGGER THRU)

Connector 3.5mm Mono mini jack × 1

Power AC120V, 60Hz

AC220 - 240V, 50/60Hz

Power consumption 210W

Standby power 0.4W

Overall dimensions 444 (W) × 111.3 (H) × 348.2 (D) mm (including protrusions)

Weight 9.9kg

Operating Temperature +5°C to +35°C

Operating Humidity Range 5% to 85% (no condensation)

Storage Temperature Range -20°C to +55°C

Included accessory Power cord, Foot pad × 3, Owner's manual

* Design and specification may subject to change without notice.

* RoHS complied