

ROTEL RCD-1572 MKII

Total Harmonic Distortion (THD) (20Hz–20kHz) <0.004%

Frequency Response

Line Level Inputs: 10Hz - 100kHz ± 0.3 dB

Digital Inputs: 20Hz - 20kHz ± 0.5 dB

Phono Input: 20Hz - 20kHz ± 0.3 dB

S/N Ratio (IHF "A" Weighted)

Line Level Inputs: 110dB

Digital Inputs: 100dB

Phono Input: 80dB

Dimensions (W × H × D) 431 × 99 × 338mm 17" × 3.9" × 13.5"

Front Panel Height 2U / 88.1mm (3.5")

Power Requirements 120V, 60Hz

Power Consumption 35W

Standby Power Consumption <0.5W

Net Weight 7.4kg (16lbs.)

BTU Rating 65 BTU/h

Intermodulation Distortion (60Hz:7kHz, 4:1) <0.004%

Input Sensitivity

Line Level Inputs (RCA): 200mV

Line Level Inputs (XLR): 300mV

Phono Input (MM): 3mV

Input Impedance

Line Level Inputs (RCA): 100k Ω

Line Level Inputs (XLR): 100k Ω

Digital Inputs: 75 Ω

Phono Input (MM): 47k Ω

Input Overload

Line Level Inputs: 4V

Phono Input: 62mV

Output Level

Unbalanced (RCA): 1V

Balanced (XLR): 2V

Tone Controls ± 10 dB at 100Hz / 10kHz

Coax/Optical Digital Input Signals

LPCM (Up to 24-bit/192kHz)

PC-USB

USB Audio Class 1 (up to 24/96)

USB Audio Class 2 (up to 32/384)*

*Driver Installation Required

DSD/DoP 1x, 2x