

Specs

Model EVERSOLO DMP-A6

Display 6" LCD touchscreen Internal Memory

4GDDR4 +32GeMMC

DAC ES 9038Q2M*2

Audio Processor XMOS XU316

Op-amp Chip OPA1642

Power Supply Low noise, high quality switching power supplies

SSD M.2 NVME 3.0 2280 protocol, up to 4TB

USB-A Port USB3.0*2

Ethernet RJ-45(10/100/1000Mbps)

WiFi WiFi 2.4G+5G dual band

Playback and DAC Decoding Support up to stereo DSD512, PCM 768KHz 32Bit, MQA

Music Service Tidal, Qobuz, Highresaudio, Amazon, WebDAV, UPnP

Streaming Air Play, DLNA, Spotify, Tidal Connect, Qobuz Connect etc.

Bluetooth Audio Input Bluetooth BT5.0, support SBC/AAC/aptX/aptX LL/aptX HD/LDAC

USB-C Audio Input USB Audio Compatibility: Windows (7, 10), Mac, Android, IOS Support up to stereo DSD512, PCM 768KHz 32Bit, MQA

Optical/Coaxial Audio Input Support up to stereo PCM 192KHz 24Bit, DSD64 Dop, MQA

Optical/Coaxial Audio Output Support up to stereo PCM 192KHz 24Bit, DSD64 Dop, MQA

HDMI Audio Output DSD64 Native multi-channel/PCM192KHz multichannel raw output(Up to 5.1)

Control Method Mobile App, Touch screen control

XLR Output Audio Characteristics

Output level: 5.2V

Frequency response: 20Hz~20KHz(± 0.15 dB)

Dynamic range: > 128dB

SNR: >128dB

THD+N: <0.00009%(-120dB) @A-wt

Crosstalk: >-125dB

RCA Output Audio Characteristics Output level: 2.6V

Frequency response: 20Hz~20KHz (± 0.2 dB)

Dynamic range: > 124dB

SNR: >124dB

THD+N: <0.00011%(-119dB)@A-WT

Crosstalk: >-124dB

PSU AC 110~240V 50/60Hz

Rated Power 13W

Dimensions L 187mm* W 270mm* H 90mm

Packing List Power cable*1, USB cable*1, Screwdriver*1, user manual*1